

Web Images Videos Maps News Shopping Gmail more ▾

[Sign in](#)

Google

vehicle subsystem mode sensor limit OR prev

[Search Patents](#)

[Advanced](#)

Patents Showing: [Any status](#) View as: [List](#) Patents 1 - 100 on vehicle subsystem m

[Sort by relevance](#) | [Sort by date \(new first\)](#) | [Sort by date \(old first\)](#)

[Fingerprint actuation of customized vehicle features](#)

US Pat. 6100811 - Filed Dec 22, 1997 - TRW Inc.

Another **mode** that may be selected by the primary user of the **vehicle** is the ... for adjusting a **vehicle subsystem** to an individually preferred setting. ...

[Method and apparatus for controlling brake-steer in an automotive vehicle in ...](#)

US Pat. 7070247 - Filed Mar 16, 2004 - Ford Global Technologies, LLC

Safety device 84 is part of a **vehicle subsystem** control. Safety device 84 may control a passive safety device 86 such as an airbag, a pressure **sensor** 89, ...

[Headlamp control to prevent glare](#)

US Pat. 6861809 - Filed Sep 5, 2002 - Gentex Corporation

A control system for controlling at least one exterior **vehicle** light of a controlled **vehicle**, the system comprising: a processor; and 15 a memory **subsystem** ...

[FIG.LOB](#)

US Pat. 3748466 - Filed Jun 14, 1971

Speed **sensor** speed **limit** permitted in that block. ... If the be brought to a safe **stop**. **vehicle** is not overspeed the speed **sensor** pulses are not 15 The ...

[Vehicle dynamics control system with varying sensor configurations](#)

US Pat. 5790970 - Filed Dec 22, 1995 - Robert Bosch GmbH

Furthermore, a gearbox control 112 is provided stabilize the **vehicle**. For this purpose, the longitudinal speed as a **subsystem**, by means of which gearbox ...

[Multi-purpose autonomous vehicle with path plotting](#)

US Pat. 5170352 - Filed Aug 7, 1991 - FMC Corporation

16) includes a position **subsystem** 82, **sensor subsystem** 66 and ... provides for **vehicle stop**, **vehicle** rotation and other low level tasks as directed by ...

[Computer peripheral floor cleaning system and navigation method](#)

US Pat. 5995884 - Filed Mar 7, 1997

Position-determination **subsystem** 151 uses processed **sensor** signals 150 and map data 45 stored on mass-storage device 20 to calculate **vehicle** 1's estimated ...

[Battery heating system using instantaneous excess capacity of a vehicle ...](#)

US Pat. 5055656 - Filed Dec 21, 1989 - Globe-Union, Inc.

Step **sensor** temperature at which heating is no longer de- S-201 provides that ... This will allow the control circuit 30 to 10 **prevent** localized as well as ...

[Supervisory diagnostics for integrated vehicle stability system](#)

US Pat. 7136729 - Filed Jul 26, 2004 - General Motors Corporation

It is also desirable to isolate the defective **sensor** or ... **sensor** signal and the road wheel angle measurement signal are below a predetermined **limit**. ...



Result Page: [1](#) [2](#) [3](#) [4](#) [5](#) [6](#) **Next**

vehicle subsystem mode sensor limit OR pre

Search Patents

Advanced Patent Search

[Google Home](#) - [About Google](#) - [About Google Patents](#) - [Google Patents Help](#)

©2009 Google